



ASEPTIC 800I 30°

Dimensions : Ø 1000 x approx. 1660 +/-15 mm height
Volume: 800 liter + 20 liters
Min./max. operating pressure: -0.5/+1.5 bar
Minx./max. operating temperature: -20/+120° C
Test pressure: +2.4 bar
Group classification: 2

Material:

AISI 304 according DIN EN 10088-2 2B

Surface treatment:
All welding seams pickled and passivated

Design according to the following description:

Top head:

- screw cover DN 400 with silicone lid or DN 400 bayonet system 6 pins
- within the cover:
 - 1 x CO²-vane DN 12 (type Kombi)
 - 1 x CO²-valve (DN 6.5) with dust cap
 - 1 x pressure relief valve +1.5 bar
 - 1 x nozzle DN 50 / DIN 11851 with silicone gasket, s.s. blind cap and wire

Bottom:

- deep drawn - 30° cone
- outlet DN 50 with K+H butterfly valve DN 50 type: G-S with silicone sealing sleeve, silicone sealing ring and blind nut (plastic HDPE) with wire rope

Marking

- lettering etched on the outlet side: Vent during discharge
- lettering etched on the outlet and back side: Foodstuff only
- sticker
- CE-name plate with numbering:

Approval

- * foodstuff conformity in compliance with directive (EG) No. 1935/2004
 - * Declaration of manufacturer and CE-sign acc. to PED requirements CE 0036
- Compatibility of tank material with product to be filled-in shall be checked and guaranteed by operator!*



ASEPTIC 800I 45°

Dimensions: Ø 1000 x approx. 1840 mm height (+/- 15mm)

Wall thickness: 2.0 mm

Capacity: 800 liters + 10 liters

min./max. operating pressure: -0.2/+1.0 bar

min./max. operating temp.: -20/+120°C

Test pressure: +1.6 bar

Group classification: 2

Material:

AISI 304 according to DIN EN 10088-2 2B

Surface treatment:

Completely bath-pickled and passivated

Design according to the following description:

Top head:

- screw cover DN 400 with silicone lid or DN 400 bayonet system 6 pins
- within the lid:
 - 1 x CO²-valve (DN 6.5) with dust cap
 - 1 x CO²-valve DN 12 (type Kombi)
 - 1 x nozzle DN 50 / DIN 11851 with silicone sealing and s.s. blind cap * 1 x pressure relief valve +1.5 bar or 2.0 bar

Bottom:

- 45° cone
- outlet DN 80 with K+H butterfly valve DN 80/DIN 11851, type G-S, silicone gasket and s.s. blind cap

Marking

- sticker
- CE-name plate with numbering:

Approval

- Foodstuff conformity in compliance with directive (EG) No. 1935/2004
 - Declaration of manufacturer and CE-sign according to PED requirements CE 0036
- Compatibility of tank material with product to be filled-in shall be checked and guaranteed by operator! As well as additional cleaning to be performed by the lessee if needed*